

ENGINEERING AND GINNING

First Stage Mote System Total Particulate Emission Factors and Rates for Cotton Gins: Method 17

Derek P. Whitelock, Michael D. Buser*, J. Clif Boykin, and Gregory A. Holt

ABSTRACT

This report is part of a project to characterize cotton gin emissions from the standpoint of stack sampling. The impetus behind this project was the urgent need to collect additional cotton gin emissions data to address current regulatory issues. A key component of this study was focused on Environmental Protection Agency (EPA) total particulate emission factors. There is no total particulate emission factor published for 1st stage mote systems in the 1996 EPA AP-42. The current AP-42 factor represents 1st and 2nd stage mote systems combined. The objective of this study was to collect total particulate emission factor data for 1st stage mote systems from cotton gins located in regions across the cotton belt using EPA-approved stack sampling methodology. The project plan included sampling seven cotton gins. Key factors for selecting specific cotton gins included: 1) facility location, 2) production capacity, 3) processing systems and 4) abatement technologies. Five gins with 1st stage mote system exhausts that were not combined with 2nd stage system exhausts were sampled. The average production rate during testing for the five gins was 27.9 bales/h. The average 1st stage mote system total particulate emission factor based on five tests (15 total test runs) was 0.025 kg/227-kg bale (0.056 lb/500-lb bale). The 1st stage mote system test average emission rates ranged from 0.31 to 1.42 kg/h (0.69-3.13 lb/h).

United States (U.S.) Environmental Protection Agency (EPA) emission factors were published in

EPA's Compilation of Air Pollution Emission Factors, AP-42 (EPA, 1996b). These factors were assigned a rating from A (Excellent) to E (Poor) that is used to assess the quality of the data being referenced. In the 1996 EPA AP-42, there are emission factors for total particulate listed for eleven common cotton gin systems. The EPA emission factor quality ratings for these data are extremely low. Cotton gin data received these low ratings because they were collected almost exclusively from a single geographical region, far western United States (EPA, 1996a). The AP-42 data are limited in that some systems commonly used in cotton gins are not represented or are combined with another system under a single emission factor (e.g. 1st and 2nd stage mote systems are represented by the mote fan). Cotton ginners' associations across the cotton belt, including the National, Texas, Southern, Southeastern, and California associations, agreed that there was an urgent need to collect additional cotton gin emissions data to address current regulatory issues. Working with the cotton ginning associations across the country and state and federal regulatory agencies, Oklahoma State University and United States Department of Agriculture-Agricultural Research Service (USDA-ARS) researchers developed a proposal and sampling plan that was initiated in 2008 to address this need for additional data. This report is part of a series that details cotton gin emissions measured by stack sampling. Each manuscript in the series addresses a specific cotton ginning system. The systems covered in the series include: unloading, 1st stage seed-cotton cleaning, 2nd stage seed-cotton cleaning, 3rd stage seed-cotton cleaning, overflow, 1st stage lint cleaning, 2nd stage lint cleaning, combined lint cleaning, cyclone robber, 1st stage mote, 2nd stage mote, combined mote, mote cyclone robber, mote cleaner, mote trash, battery condenser and master trash. This report focuses on total particulate emissions from 1st stage mote systems.

There are no 1996 EPA AP-42 emission factors for 1st stage mote systems (EPA, 1996b). First stage mote systems would be similar to the mote fan listed in AP-42, but the AP-42 factor represents 1st and 2nd stage mote systems combined. The 1996 EPA AP-42 average total particulate emission factor for the mote

D.P. Whitelock, USDA-AR Southwestern Cotton Ginning Research Laboratory, 300 E College, P.O. Box 578, Mesilla Park, NM 88047; M.D. Buser*, Biosystems and Agricultural Engineering Oklahoma State University, 214 Agricultural Hall; Stillwater, OK 74078; J.C. Boykin, USDA-ARS Cotton Ginning Research Unit, 111 Experiment Station Road, P.O. Box 256, Stoneville, MS 38776; and G.A. Holt, USDA-ARS Cotton Production and Processing Research Unit, 1604 E FM 1294, Lubbock, TX 79403

*Corresponding author: buser@okstate.edu

fan (combined 1st and 2nd mote systems) was 0.13 kg (0.28 lb) per 217-kg [480-lb] equivalent bale with a range of 0.045 to 0.47 kg (0.099-1.0 lb) per bale (EPA, 1996a, 1996b). This average and range was based on nine tests conducted in one geographical location. The EPA emission factor quality rating was D, which is the second lowest possible rating (EPA, 1996a).

Seed-cotton is a perishable commodity that has no real value until the fiber and seed are separated (Wakelyn et al., 2005). Cotton must first be processed or ginned at the cotton gin to separate the fiber and seed, producing 227-kg (500-lb) bales of marketable cotton fiber. Cotton ginning is considered an agricultural process and an extension of the harvest by several federal and state agencies (Wakelyn et al., 2005). Although the main function of the cotton gin is to remove the lint fiber from the seed, many other processes also occur during ginning, such as cleaning, drying, and packaging the lint. Pneumatic conveying systems are the primary method of material handling in the cotton gin. As material reaches a processing point, the conveying air is separated and emitted outside the gin through a pollution control device. The amount of dust emitted by a system varies with the process and the condition of the material in the process.

Cotton ginning is a seasonal industry lasting from 75 to 120 days, depending on the size and condition of the crop. Although the trend for U.S. cotton production remained generally flat at about 17 million bales per year during the last 20 years, annual production varied greatly for various reasons, including climate and market pressure (Fig. 1). The number of active gins in the U.S. has not remained constant, but has steadily declined to fewer than 700 in 2011. Consequently, the average volume of cotton handled by each gin has risen and gin capacity has increased to an average of about 25 bales per hour across the U.S. cotton belt (Valco et al., 2003, 2006, 2009, 2012).

The typical cotton gin facility includes: unloading system, dryers, seed-cotton cleaners, gin stands, overflow collector, lint cleaners, battery condenser, bale packaging system, and trash handling systems (Fig. 2); however, the number and type of machines and processes varies. Each of these systems serves a unique function with the ultimate goal of ginning the cotton to produce a marketable product. Raw seed-cotton harvested from the field is compacted into large units called modules for delivery to the gin. The unloading system removes seed-cotton either mechanically or pneumatically from the module feed system and conveys the seed-cotton to the seed-cotton cleaning systems. Seed-cotton cleaning systems dry the seed-cotton

and remove foreign matter prior to ginning. Ginning systems also remove foreign matter and separate the cotton fiber from the seed. Lint cleaning systems further clean the cotton lint after ginning. The battery condenser and packaging systems combine lint from the lint cleaning systems and compress the lint into dense bales for easy transport. Gin systems produce some type of by-product or trash, such as rocks, soil, sticks, hulls, leaf material, and short or tangled immature fiber (motes), as a result of processing the seed-cotton or lint. These streams of by-products must be removed from the machinery and handled by trash collection systems. These trash systems typically further process the by-products (e.g., mote cleaners) and/or consolidate the trash from the gin systems into a hopper or pile for subsequent removal.




Figure 1. Annual U.S. cotton production, active U.S. gins, and average ginning volume (bales per gin) (NASS, 1993-2012).




Figure 2. Typical modern cotton gin layout (Courtesy Lummus Corporation, Savannah, GA).

After the seed and lint are separated at the gin stand, the lint is cleaned by one or more stages of lint cleaners. The material removed by lint cleaning is referred to as motes and is handled by the mote systems (Fig. 3). Motes are pneumatically conveyed by suction away from the lint cleaners, through a centrifugal fan, to one or two particulate abatement cyclones. Depending on the gin facility, the 1st and 2nd stages of lint cleaning may share a mote system, thus sharing a fan and abatement devices, or lint cleaning stages may have mote systems that operate independently with separate fans and cyclones, denoted as 1st stage mote systems or 2nd stage mote systems. The material handled by the mote system cyclones typically includes small trash and particulate, and large amounts of lint fibers (Fig. 4).




Figure 3. Typical cotton gin first stage mote system layout (Courtesy Lummus Corporation, Savannah, GA).



Figure 4. Photograph of typical trash captured by the first stage mote cyclones.

Cyclones are the most common particulate matter (PM) abatement devices used at cotton gins. Standard cyclone designs used at cotton ginning facilities are the 2D2D and 1D3D (Whitelock, et al., 2009). The first D in the designation indicates the length of the cyclone barrel relative to the cyclone barrel diameter and the second D indicates the length of the cyclone cone relative to the cyclone barrel diameter. A standard 2D2D cyclone (Fig. 5) has an inlet height of D/2 and width of D/4 and design inlet velocity of 15.2 ± 2 m/s (3000 ± 400 fpm). The standard 1D3D cyclone (Fig. 5) has the same inlet dimensions as the 2D2D or may

have the original 1D3D inlet with height of D and width D/8. Also, it has a design inlet velocity of 16.3 ± 2 m/s (3200 ± 400 fpm).




Figure 5. 2D2D and 1D3D cyclone schematics.

The objective of this study was to collect total particulate emission factor data for 1st stage mote systems with cyclones for emissions control at cotton gins located in regions across the cotton belt based on EPA-approved stack sampling methodologies.

METHODS

Two advisory groups were established for this project. The industry group consisted of cotton ginning industry leaders and university and government researchers. The air quality group included members from state and federal regulatory agencies, and university and government researchers. Both groups were formed to aid in project planning, gin selection, data analyses, and reporting. The project plan was described in detail by Buser et al. (2012).

Seven cotton gins were sampled across the cotton belt. Key factors for selecting specific cotton gins included: 1) facility location, 2) production capacity, 3) processing systems and 4) abatement technologies. Operating permits, site plans, and aerial photographs were reviewed to evaluate potential sites. On-site visits were conducted on all candidate gins to evaluate the process systems and gather information including system condition, layout, capacities, and standard operation. Using this information, several gins from each selected geographical region were selected and prioritized based on industry advisory group discussions. Final gin selection from the prioritized list was

influenced by crop limitations and adverse weather events in the region.

Based on air quality advisory group consensus, EPA Method 17 (CFR, 1978) was used to sample the 1st stage mote system at each gin. Method 17 was selected over Method 5 (CFR, 1987) because of the relatively low stack temperatures found at cotton gins. Method 5 requires a heated glass probe and filter holder to maintain the sampled gas temperature of 120°C (248°F). Key benefits of using Method 17 over Method 5 occur when particulate concentrations are independent of temperature and the sampled gas contains no liquid droplets or is not saturated with water vapor, the heating systems can be eliminated and sampling can occur at stack temperature with an in-stack filter. Methodology for sampling total particulate called for withdrawing particulate-laden stack gas isokinetically (the velocity of the gas entering the sampler was equal to the velocity of the gas in the stack) through a button-hook nozzle and then collecting particles on an in-stack filter (Fig. 6). The methods for retrieving the filter and conducting acetone washes of the sampling nozzle are described in Method 17 (CFR, 1978). The mass of particulate on the filter and in the nozzle wash was determined by gravimetric analyses. The total particulate mass was determined by summing the mass of particulates on the filter and the front half wash. Stack gas temperature and moisture content were also measured using EPA Method 17.




Figure 6. EPA Method 17 total particulate button-hook nozzle and in-stack filter holder photograph.

Only one stack from each 1st stage mote system was tested. For systems with multiple stacks, it was assumed that emissions from each stack of the system were equivalent. The total particulate emissions for the system were calculated by multiplying the measured emission rates by the total number of cyclones used to control the process tested (EPA, 1996a). To obtain reliable results, the same technician from the same certified stack sampling company (Reliable

Emissions Measurements, Auberry, CA), trained and experienced in stack sampling cotton gins, conducted all the tests at all the cotton gins.

All stack sampling equipment was purchased from Apex Instruments (Fuquay-Varina, NC) and met Method 17 specifications. The sampling media were 47 mm Zeflur filters (Pall Corporation, Port Washington, NY) and the sample recovery and analytical reagent was American Chemical Society certified acetone (A18-4, Fisher Chemical, Pittsburgh, PA – assay \geq 99.5%). Filters and wash tubs and lids were pre-labeled and pre-weighed and stored in sealed containers at the USDA-Agricultural Research Service Air Quality Lab (AQL) in Lubbock, TX, and then transported to each test site. Prior to testing, the technician calibrated all sampling equipment according to EPA Method 17.

Each cyclone selected for testing was fitted with a cyclone stack extension that incorporated two sampling ports (90° apart) and airflow straightening vanes to eliminate the cyclonic flow of the air exiting the cyclone (Fig. 7). The extensions were designed to meet EPA criteria (EPA, 1989) with an overall length of 3 m (10 ft) and sampling ports 1.2-m (48-in) downstream from the straightening vanes and 0.9-m (36-in) upstream from the extension exit.




Figure 7. Schematic and photographs of stack extensions with sampling port and straightening vanes (rail attached to extension above sampling port, at right, supports sampling probe during testing traverse).

The tests were conducted by the technician in an enclosed sampling trailer at the base of the cyclone bank (Fig. 8). Sample retrieval, including filters and nozzle acetone washes, was conducted according to Method 17. After retrieval, filters were sealed in individual Petri dishes and acetone washes were dried on-site in a conduction oven at 49°C (120°F) and then sealed with pre-weighed lids and placed in individual plastic bags for transport to the AQL in Lubbock, TX for gravimetric analyses. During testing, bale data (ID number, weight, and date/time of bale pressing) were either manually recorded by the bale press operator or captured electronically by the gin’s computer system for use in calculating emission factors in terms of kg/227-kg bale (lb/500-lb bale). Emission factors and rates were calculated in accordance with Method 17 and American Society of Agricultural Engineers (ASAE) Standard S582 (ASABE, 2005).




Figure 8. Clockwise from top right: cotton gin stack sampling with air quality lab trailer and technicians on lifts; certified stack sampling technician in the trailer control room conducting tests; sample recovery in trailer clean room; technician operating the probe at stack level.

All laboratory analyses were conducted at the AQL. All filters were conditioned in an environmental chamber ($21 \pm 2^\circ\text{C}$ [$70 \pm 3.6^\circ\text{F}$]; $35 \pm 5\%$ RH) for 48 h prior to gravimetric analyses. Filters were weighed in the environmental chamber on a Mettler MX-5 microbalance (Mettler-Toledo Inc., Columbus, OH – $1 \mu\text{g}$ readability and $0.9 \mu\text{g}$ repeatability) after being passed through an anti-static device. The MX-5 microbalance was leveled on a marble table and housed inside an acrylic box to minimize the effects of air currents and vibrations. To reduce recording errors, weights were electronically transferred from the microbalance

directly to a spreadsheet. Technicians wore latex gloves and a particulate respirator mask to avoid contamination. AQL procedures required that each sample be weighed three times. If the standard deviation of the weights for a given sample exceeded $10 \mu\text{g}$, the sample was reweighed. Gravimetric procedures for the acetone wash tubs were the same as those used for filters.

In addition to gravimetric analyses, each sample was visually inspected for unusual characteristics, such as cotton lint content or extraneous material. Digital pictures were taken of all filters and washes for documentation purposes. After the laboratory analyses were completed all stack sampling, cotton gin production, and laboratory data were merged.

Five of the seven gins (A, B, C, D and F) sampled had 1st stage mote systems that were not combined with 2nd stage mote systems. The 1st stage mote systems sampled were typical for the industry, but varied among the gins. As the lint was cleaned in three 1st stage lint cleaning systems at gin A, the trash removed from the lint was combined in the 1st stage mote system and pneumatically conveyed from the lint cleaners through a fan and exhausted through one or more cyclones (Fig. 9). The 1st stage mote system at gin C was essentially the same, except the 1st stage mote system pulled trash from two 1st stage lint cleaning systems (Fig. 10). The 1st stage mote systems at gins B, D, and F were also similar, but the systems at those gins pulled material from four 1st stage lint-cleaning systems (Fig. 11).




Figure 9. Schematic of first stage mote system pulling material from three first stage lint cleaners (gin A).




Figure 10. Schematic of first stage mote system pulling material from two first stage lint cleaners (gin C).




Figure 11. Schematic of first stage mote system pulling material from four first stage lint cleaners (gins B, D, and F).

All 1st stage mote systems sampled utilized 1D3D cyclones to control emissions (Fig. 5), but there were some cyclone design variations among the gins (Table 1 and Fig. 12). Gins D and F split the system exhaust flow between two cyclones in a dual configuration (side-by-side as opposed to one-behind-another). The system airstream for gins A, B and C was exhausted through a single cyclone. Inlets on the 1st stage mote cyclones for gins B, D and F were 2D2D type, while gins A and C had inverted 1D3D inlets. Standard cones were present on 1st stage mote cyclones at all gins, except gin B, which had an expansion chamber. The cyclones tested at gins A, B, D and F had mote cyclone robber systems pulling airflow from their trash exits. This configuration helps remove lint and other trash from the cyclone that could otherwise circulate near the trash exit at the bottom of the cone for a period of time before dropping out. All of the cyclone variations outlined above, if properly designed and maintained, are recommended for controlling cotton gin emissions (Whitelock et al., 2009).



Figure 12. Cyclone design variations for the tested systems (left to right): dual configuration that splits flow between identical 1D3D cyclones with 2D2D inlets; 1D3D cyclone with an inverted 1D3D inlet; 1D3D cyclone with 2D2D inlet and expansion chamber on the cone; 1D3D cyclone with 2D2D inlet and standard cone.

Table 1. Abatement device configuration² for first stage mote systems tested.

Gin	Cyclone Type	Inlet Design ³	Systems per Gin	Cyclones per Gin	Configuration	Cone Design	Trash Exit ^x
A	1D3D	inverted 1D3D	1	1	single	standard	robber
B	1D3D	2D2D	1	1	single	expansion chamber	robber
C	1D3D	inverted 1D3D	1	1	single	standard	hopper
D	1D3D	2D2D	1	2	dual	standard	robber
F	1D3D	2D2D	1	2	dual	standard	robber

² Figures 5 and 12

³ Inverted 1D3D inlet has duct in line with the bottom of the inlet

^x Systems to remove material from cyclone trash exits: hopper = large storage container directly under cyclone trash exit; robber = pneumatic suction system

RESULTS

Table 2 shows the test parameters for each Method 17 test run for the 1st stage mote systems sampled at the five gins. The average ginning rate for the five gins was 27.9 bales/h and the test average ginning rate at each gin ranged from 21.2 to 35.7 bales/h (based on 227-kg [500-lb] equivalent bales). The capacity of gins sampled was representative of the industry average, approximately 25 bales/h. The 1D3D cyclones were all operated with inlet velocities within design criteria, 16.3 ± 2 m/s (3200 ± 400 fpm).

There are criteria specified in EPA Method 17 for test runs to be valid for total particulate measurements (CFR, 1978). Isokinetic sampling must fall within the EPA defined range of $100 \pm 10\%$. All tests met the isokinetic criteria (Table 2). The stack gas temperatures ranged from 23 to 41°C (73-106°F) and moisture content ranged from 0.2 to 2.7% wet basis (w.b.).

Total particulate emissions data (emission rates and corresponding emission factors) for the 1st stage mote system are shown in Table 3. The system average emission factor for the five gins was 0.025 kg/bale (0.056 lb/bale). The test average emission factors ranged from 0.012 to 0.041 kg (0.026-0.089 lb) per bale. The average 1st stage mote system total particulate emission factor for this project was about 20% of that published in the current 1996 EPA AP-42 for the mote fan (0.13 kg/bale [0.28 lb/bale]) (EPA, 1996a, b), which is an equivalent system to a combined 1st and 2nd stage mote system. The range of test average total particulate emission factors determined for this project was lower than the AP-42 emission factor data range for the mote fan. The test average emission rates ranged from 0.31 to 1.42 kg/h (0.69-3.13 lb/h).

Table 2. Cotton gin production data and stack sampling performance metrics for the first stage mote system.

Gin	Test Run	Ginning Rate, bales/h ^a	Cyclone Inlet Velocity,		Isokinetic Sampling, %	Stack Gas		
			m/s	fpm		Moisture Content, % w.b.	Temperature	
							°C	°F
A	1	24.9	16.3	3207	100	1.2	25	77
	2	25.4	16.4	3228	93	0.8	26	78
	3	25.9	16.9	3326	96	0.2	28	83
	Test Average	25.4	16.5	3254				
B	1	25.5	17.7	3476	108	2.7	41	106
	2	12.0	18.3	3597	108	2.6	41	105
	3	26.0	17.6	3457	103	2.0	39	103
	Test Average	21.2	17.8	3510				
C	1	22.9	17.6	3468	93	1.3	26	79
	2	22.2	17.6	3465	93	1.2	28	83
	3	23.2	17.4	3425	98	1.7	32	89
	Test Average	22.8	17.5	3453				
D	1	33.7	14.8	2922	96	1.9	31	88
	2	37.1	14.9	2938	96	1.3	32	90
	3	36.4	15.1	2976	98	1.1	31	88
	Test Average	35.7	15.0	2946				
F	1	32.9	17.4	3435	91	1.2	23	73
	2	34.0	17.3	3405	93	1.5	26	79
	3	35.7	17.4	3423	93	1.0	28	82
	Test Average	34.2	17.4	3421				
System Average		27.9	16.8	3317				

^a 227 kg (500 lb) equivalent bales

Table 3. Total particulate emissions data for the first stage mote system.

Gin	Test Run	Emission Rate,		Emission Factor,	
		kg/h	lb/h	kg/bale ^z	lb/bale ^z
A	1	0.98	2.15	0.039	0.086
	2	1.02	2.26	0.040	0.089
	3	1.09	2.40	0.042	0.093
	Test Average (n=3)	1.03	2.27	0.041	0.089
B	1	0.44	0.96	0.017	0.038
	2	0.27	0.60	0.023	0.050
	3	0.53	1.16	0.020	0.045
	Test Average (n=3)	0.41	0.91	0.020	0.044
C	1	0.33	0.73	0.014	0.032
	2	0.41	0.90	0.018	0.041
	3	0.20	0.43	0.0085	0.019
	Test Average (n=3)	0.31	0.69	0.014	0.030
D	1	1.72	3.80	0.051	0.113
	2	1.17	2.59	0.032	0.070
	3	1.37	3.01	0.038	0.083
	Test Average (n=3)	1.42	3.13	0.040	0.088
F	1	0.37	0.82	0.011	0.025
	2	0.37	0.82	0.011	0.024
	3	0.45	0.98	0.012	0.028
	Test Average (n=3)	0.40	0.88	0.012	0.026
System Average (n=5)				0.025	0.056

^z 227 kg (500 lb) equivalent bales

Figure 13 shows an example of samples recovered from a typical 1st stage mote system test run. Often, there were cotton lint fibers in the cotton gin cyclone exhausts. Therefore, it was not unusual to find lint fiber on the Method 17 filter or in the front half wash, which was included in the total particulate emissions.




Figure 13. Typical EPA Method 17 filter and sampler head acetone wash from the first stage mote system with lint fiber on the filter (indicated by arrow). From left to right: front half wash and filter.

SUMMARY

Five cotton gins with 1st stage mote systems were sampled using EPA Method 17 to collect total particulate emission factor data ratings for cotton

gins. Each of the gins had 1st stage mote system exhausts that were not combined with 2nd stage mote system exhausts. The tested systems were similar in design and typical of the ginning industry. The system exhausts were equipped with 1D3D cyclones for emissions control with some variations in inlet and cone design. The average production rate during testing for the five gins was 27.9 bales/h. The average 1st stage mote system total particulate emission factor based on the five gins tested (15 total test runs) was 0.025 kg/227-kg bale (0.056 lb/500-lb bale). The gin test average emission rates ranged from 0.31 to 1.42 kg/h (0.69-3.13 lb/h).

ACKNOWLEDGEMENT

The authors appreciate the cooperating gin managers and personnel who generously allowed and endured sampling at their gins. In addition, we thank California Cotton Ginners' and Growers' Association, Cotton Incorporated, San Joaquin Valleywide Air Pollution Study Agency, Southeastern

Cotton Ginners' Association, Southern Cotton Ginners' Association, Texas Cotton Ginners' Association, Texas State Support Committee, and The Cotton Foundation for funding this project. This project was supported in-part by the USDA National Institute of Food and Agriculture Hatch Project OKL02882. The authors also thank the Cotton Gin Advisory Group and Air Quality Advisory Group for their involvement and participation in planning, execution, and data analysis for this project that is essential to developing quality data that will be used by industry, regulatory agencies, and the scientific community. The advisory groups included: the funding agencies listed above, California Air Resources Board, Missouri Department of Natural Resources, National Cotton Council, National Cotton Ginners' Association, North Carolina Department of Environment and Natural Resources, San Joaquin Valley Air Pollution Control District, Texas A&M University, Texas Commission on Environmental Quality, USDA-NRCS National Air Quality and Atmospheric Change, and U.S. Environmental Protection Agency (national, Region 4 and 9).

DISCLAIMER

Mention of trade names or commercial products in this publication is solely for the purpose of providing specific information and does not imply recommendation or endorsement by the Oklahoma State University or U.S. Department of Agriculture. Oklahoma State University and USDA are equal opportunity providers and employers.

The statements and conclusions in this report are those of the USDA-ARS and Oklahoma State University and not necessarily those of the California Air Resources Board, the San Joaquin Valleywide Air Pollution Study Agency, or its Policy Committee, their employees or their members. The mention of commercial products, their source, or their use in connection with material reported herein is not to be construed as actual or implied endorsement of such products.

REFERENCES

- American Society of Agricultural and Biological Engineers (ASABE). 2005. Cotton Gins – Method of Utilizing Emission Factors in Determining Emission Parameters. ASAE S582 March 2005. American Society of Agricultural and Biological Engineers, St. Joseph, MI.
- Buser, M.D., D.P. Whitelock, J.C. Boykin, and G.A. Holt. 2012. Characterization of cotton gin particulate matter emissions—Project plan. *J. Cotton Sci.* 16:105–116.
- Code of Federal Regulations (CFR). 1978. Method 17—Determination of particulate emissions from stationary sources (in-stack filtration method). 40 CFR 60 Appendix A-6. Available at <http://www.epa.gov/ttn/emc/promgate/m-17.pdf> (verified August 2012).
- Code of Federal Regulations (CFR). 1987. Method 5—Determination of particulate matter emissions from stationary sources. 40 CFR 60 Appendix A-3. Available at <http://www.epa.gov/ttn/emc/promgate/m-05.pdf> (verified August 2012).
- Environmental Protection Agency (EPA). 1989. Particulate sampling in cyclonic flow. U.S. Environmental Protection Agency, Washington, DC. Available online at <http://www.epa.gov/ttn/emc/guidlnd/gd-008.pdf> (verified 2 Jan. 2013).
- Environmental Protection Agency (EPA). 1996a. Emission factor documentation for AP-42, Section 9.7, Cotton Ginning, (EPA Contract No. 68-D2-0159; MRI Project No. 4603-01, Apr. 1996).
- Environmental Protection Agency (EPA). 1996b. Food and agricultural industries: Cotton gins. *In* Compilation of air pollution emission factors, Volume 1: Stationary point and area sources. Publ. AP-42. U.S. Environmental Protection Agency, Washington, DC.
- National Agricultural Statistics Service (NASS). 1993–2012. Cotton Ginnings Annual Summary [Online]. USDA National Agricultural Statistics Service, Washington, DC. Available at <http://usda.mannlib.cornell.edu/MannUsda/viewDocumentInfo.do?documentID=1042> (verified 2 Jan. 2013).
- Valco, T.D., H. Ashley, J.K. Green, D.S. Findley, T.L. Price, J.M. Fannin, and R.A. Isom. 2012. The cost of ginning cotton – 2010 survey results. p. 616–619 *In* Proc. Beltwide Cotton Conference., Orlando, FL 3-6 Jan. 2012. Natl. Cotton Counc. Am., Cordova, TN.
- Valco, T.D., B. Collins, D.S. Findley, J.K. Green, L. Todd, R.A. Isom, and M.H. Wilcutt. 2003. The cost of ginning cotton – 2001 survey results. p. 662–670 *In* Proc. Beltwide Cotton Conference., Nashville, TN 6-10 Jan. 2003. Natl. Cotton Counc. Am., Memphis, TN.
- Valco, T.D., J.K. Green, R.A. Isom, D.S. Findley, T.L. Price, and H. Ashley. 2009. The cost of ginning cotton – 2007 survey results. p. 540–545 *In* Proc. Beltwide Cotton Conference., San Antonio, TX 5-8 Jan. 2009. Natl. Cotton Counc. Am., Cordova, TN.

Valco, T.D., J.K. Green, T.L. Price, R.A. Isom, and D.S. Findley. 2006. Cost of ginning cotton – 2004 survey results. p. 618–626 *In Proc. Beltwide Cotton Conference.*, San Antonio, TX 3-6 Jan. 2006. Natl. Cotton Counc. Am., Memphis, TN.

Wakelyn, P.J., D.W. Thompson, B.M. Norman, C.B. Nevius, and D.S. Findley. 2005. Why Cotton Ginning is Considered Agriculture. *Cotton Gin and Oil Mill Press* 106(8): 5-9.

Whitelock, D.P., C.B. Armijo, M.D. Buser, and S.E. Hughs. 2009 Using cyclones effectively at cotton gins. *Appl. Eng. Ag.* 25:563–576.